

Interactive 3D Tangible Display with a High-Speed Stiffness-Variable Jamming Module

"Transforming Static Art into Tactile Experience Through Magnetic Jamming"


Chanyoung Ahn, Jaesung Lee, Donghyun Hwang[†]


{chanyoung.ahn; jay.lee; donghyun}@kist.re.kr

NTRODUCTION

Research Aim

- Transform conventional untouchable static art into interactive art by developing a 3D tangible display.
- Using a stiffness-variable surface based on magnetic jamming, we provide a \checkmark more immersive and tactile artistic experience.





EXPERIMENTAL EVALUATION


Durability Under High–Payload Condition





- ✓ When an electric current is applied to the electromagnet, it induces magnetic attraction among the soft magnetic particles, thereby increasing the stiffness and preserving the deformed shape.
- ✓ This mechanism is compact and lightweight, making it suitable for integration into traditional artworks without compromising their aesthetic value.

Structural Configuration of Overall Artwork



- **1 Embedded speaker**
- 2 Wooden Hahoetal mask
- **3 Magnetic jamming module**
- 4 Hanji-covered Hahoetal
- **5** Chin module with servo motor
- **6 Ultrasonic distance sensor**
- 7 External switch for toggling



Two type of jamming Module

Structural Configuration of Jamming Module

Customizing Jamming Module & Composition



	(Unit: g)		Iron Granular	Iron Powder	Oil	Silicone
	Nose	Membrane	-	15	-	25
		Particles	182	78	20	-
	Cheek	Membrane	-	38.3	-	12.7
		Particles	38.5	38.3	3	-


Korea Traditional Heritage


Time [ms]





These are traditional Korean *Hahoetal* masks from Andong, symbolizing various characters in folk performances. They are crafted using Hanji, traditional Korean paper made from mulberry trees.







- We present a stiffness-variable 3D tangible display integrated with traditional Korean mask art.
- This fusion of art and technology enables **user interaction and real-time** haptic feedback, offering a new dimension in cultural appreciation.

ACKNOWLEDGEMENT

This work was supported in part by the Samsung Science and Technology Foundation under Grant SRFC-IT2202-01, and in part by the Korea Institute of Science and Technology Institutional Program.



2025 IEEE International Conference on Robotics & Automation 19 – 23 May, Atlanta, USA

